REMARKS

Claims 1-8 are currently being examined in the present application. Claim 1 is the sole

independent claim. Claims 1, 4, and 5 have been amended to more distinctly claim and point out

the applicant's invention. Claim 6 has been canceled. It is asserted that no new matter is

contained herein and that these amendments, along with the accompanying remarks, are fully

responsive to the office action dated May 21, 2008.

The Examiner has rejected claims 1-6 under 35 U.S.C. § 102(b) as being anticipated by

Johnson (U.S. Patent No. 3,812,682). Claim 6 is canceled through this amendment, making the

rejection to claim 6 moot.

The Examiner's position regarding Johnson is found on page 2 of the present action. The

Examiner's position is summarized in that <u>Johnson</u> discloses in Fig. 13 a pair of cylinders 142

and 143, which are shown as being disposed in parallel. Each cylinder contains therein a

displacer piston 144 (or 151) and a power piston 146 (or 152). The opposite ends of each

cylinder are in communication with a heat exchanger 162, which is made up of a heater H, a

regenerator R and a cooler C. Although the two heat exchangers 162 are shown between the two

cylinders 142 and 143 in Fig. 13, this merely teaches that the two heat exchangers 162 are

located between the two cylinders 142 and 143.

-5-

Reply to OA dated May 21, 2008

The examiner has further rejected claims 1-6 under 35 U.S.C. § 102(b) as being

anticipated by Joynes et al. (U.S. Patent No. 4,020,635). Claim 6 is canceled through this

amendment, making the rejection to claim 6 moot.

The Examiner's position regarding Joynes et al. is described on page 2 of the present

action. This position is summarized in that <u>Joynes et al.</u> discloses in Fig. 1 a pair of cylinders 1

and 2 that are shown as being disposed in parallel, similar to Johnson. Each cylinder contains

therein a displacer piston 5 (or 6) and a power piston 7 (or 8). The opposite ends of the cylinder

I are in communication with a heat exchanger, which is made up of a heater 29, a regenerator 33

and a cooler 31. The opposite ends of the other cylinder 2 are in communication with a heat

exchanger, which is made up of a heater 30, a regenerator 34 and a cooler 32. The heat

exchanger cooperating with the cylinder 1 integrally attached thereto, while the other heat

exchanger cooperating with the cylinder 2 is also integrally attached thereto.

More particularly, it is the applicant's view that in <u>Joynes et al.</u>, the two heat exchangers

are spaced apart and are connected through pipes. The cooling liquid used in liquid hydrogen

stored in a tank 38. The tank 38 sends out the liquid hydrogen and supplies the same to the left-

side cooler 31. The same liquid hydrogen is assumed to be supplied also to the right-side cooler

32. The liquid hydrogen supplied to the left-side cooler 31 cools the working fluid and is heated

by the working fluid. The heated hydrogen is then supplied through a pipe 41 to a combustion

-6-

Reply to OA dated May 21, 2008

chamber 42 and is burned therein to produce a combustion gas. The combustion gas is sent via a

pipe 46 to the left-side heater 29 to heat the working fluid and is discharged to the outside

through a pipe 47. Similarly, the combustion gas produced in the combustion chamber 42 is

supplied through a pipe 50 to the right-side heater 30. It is to be noted that the two cylinders 1

and 2 are spaced apart by a sufficient distance from each other to provide a space for the

combustion chamber 42 and the connecting pipes between the two cylinders 1 and 2.

In contrast to the references cited by the Examiner, the multistage Stirling engine, as

claimed in the present application, calls for:

A. a plurality of heat exchangers including adjacent cylinders (4, 5) disposed in parallel

arrangement;

B. heat exchangers (40, 41) being each in the form of a stack of each heater, each

regenerator, and each cooler;

C. two of the heat exchangers (40, 41) forming adjacent stacks are interposed closely

between adjacent two cylinders of the plurality of cylinders (4, 5) to form an integral

structure having a shape of a flat rectangular solid including adjacent cylinders (4, 5) and

the heat exchangers (40, 41).

Of the above listed features of the invention, C is particularly important. The

combination of these features is not taught by Johnson or Joynes et al., either singularly or in

concert.

-7-

According to Claim 1 as presently amended, the two heat exchangers are formed as a

stack and are interposed closely between the adjacent two cylinders in such a manner as to form

an integral structure having a shape of a flat rectangular solid including the adjacent cylinders (4,

5) and the heat exchangers (40, 41). This means that the spacing between the two adjacent

cylinders is equal to the combined size of the two heat exchangers, so that the two heat

exchangers are closely fitted in a space between the adjacent cylinders. It will be readily

understood that in either Johnson or Joynes et al., that the heat exchangers only partly occupy the

space between the two adjacent cylinders.

This feature of claim 1 finds support in the paragraph bridging pages 16 and 17 of the

specification, and is advantageous, for among other reasons, in that the Stirling engine can be

produced in a compact structure having a simple shape of a flat rectangular solid with small

dimensions, whereby the engine can be easily installed into a small engine compartment of a

vehicle. This structure of claim 1, and also claims 2-5 through their ultimate dependence on

claim 1, provides its associated benefit in a manner not contemplated or suggested by either

Johnson or Joynes et al..

Based on the amendments to claims 1, 4, and 5, along with the preceding remarks, claims

1-5 are now believed to be patentable. Withdrawal of the rejections of claims 1-5 under 35

U.S.C. § 102(b) are now in order and respectfully solicited.

-8-

U.S. Patent Application Serial No. 10/553,237

Response filed August 21, 2008

Reply to OA dated May 21, 2008

The examiner has rejected claims 7-8 under 35 U.S.C. § 103(a) as being unpatentable

over Johnson (U.S. Patent No. 3,812,682), and also rejected these claims under 35 U.S.C. §

103(a) for being unpatentable over Joynes et al. (U.S. Patent No. 4,020,635). The Examiner in

making this rejection acknowledges that neither Johnson, nor Joynes et al., discloses the specific

location of the generator and heat exchangers in the same unit, but asserts that a person having

ordinary skill in the art would understand the inventions of claims 7 and 8 to be obvious in light

of the cited disclosures.

Due to claims 7 and 8 depending upon claims 1 and 2, which are now patentable, claims

7 and 8 are also now believed to be similarly patentable. As such, withdrawal of the outstanding

rejections to claims 7 and 8 under 35 U.S.C. § 103(a) is now in order and respectfully solicited.

-9-

U.S. Patent Application Serial No. 10/553,237

Response filed August 21, 2008

Reply to OA dated May 21, 2008

Claims 1-5, 7 and 8 are now in condition for allowance, which action, at an early date, is

requested.

If, for any reason, it is felt that this application is not now in condition for allowance, the

Examiner is requested to contact the applicants undersigned attorney at the telephone number

indicated below to arrange for an interview to expedite the disposition of this case.

In the event that this paper is not timely filed, the applicants respectfully petition for an

appropriate extension of time. Please charge any fees for such an extension of time and any

other fees that may be due with respect to this paper, to Deposit Account No. 01-2340.

Respectfully submitted,

KRATZ, QUINTOS & HANSON, LLP

/ Jason T. Somma

Attorney for Applicants

Reg. No. 61,526

Atty. Docket No. 050649

Suite 400

1420 K Street, N.W.

Washington, D.C. 20005

(202) 659-2930 ext. 211

23850

PATENT & TRADEMARK OFFICE